

## DEEP

- High performing blackout fabric with a light sheen and black reverse
- Standard 100 by Oeko-Tex® certified, free from harmful substances
- Washable up to 60°
- Proven acoustic properties

### APPLICATIONS



Not suitable:  
SG 4905

### FABRIC PROPERTIES

|                                                                                     |           |
|-------------------------------------------------------------------------------------|-----------|
|    | Blackout  |
|   | Polyester |
|  | 325 g/m²  |
|  | 0.45 mm   |
|   | 290 cm    |
|  | 295 cm    |
|  | 295 cm    |

### WASHING INSTRUCTIONS

|                                                                                     |                                                                                     |                                                                                     |                                                                                     |                                                                                     |                                                                                     |                                                                                     |
|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
|  |  |  |  |  |  |  |
|   |  |  |  |  |  |                                                                                     |
|   |  |  |  |  |  |                                                                                     |

### FEATURES / TECHNICAL PROPERTIES

|                                                                                     |                            |
|-------------------------------------------------------------------------------------|----------------------------|
|    | 5                          |
|   | Alpha-w = 0.30 / 0.55      |
|  | Flame retardant            |
|  | Applicable in humid areas  |
|  | Suitable for Wave          |
|  | Only with lined fabric     |
|  | Oeko-Tex                   |
|  | Special colours from 240 m |

### FLAME RETARDANT

Class 1 (EN 13773)  
Type B (BS 5867-2)  
CAN/ULC-S109-14



## Deep

### OPTICAL AND SOLAR COEFFICIENTS ( $\pm 5\%$ , DIN EN 410)

| Colour | $T_s$ | $R_s$ | $A_s$ | $F_c$ | $g_{tot}$ |
|--------|-------|-------|-------|-------|-----------|
| 01     | 0.0   | 4.1   | 95.9  | 0.89  | 0.64      |
| 02     | 0.0   | 4.1   | 95.9  | 0.89  | 0.64      |
| 03     | 0.0   | 4.1   | 95.9  | 0.89  | 0.64      |
| 05     | 0.0   | 4.1   | 95.9  | 0.89  | 0.64      |
| 06     | 0.0   | 4.1   | 95.9  | 0.89  | 0.64      |
| 07     | 0.0   | 3.2   | 96.8  | 0.90  | 0.65      |
| 08     | 0.0   | 3.2   | 96.8  | 0.90  | 0.65      |
| 10     | 0.0   | 3.9   | 96.1  | 0.89  | 0.64      |

$T_s$  Solar transmission

$A_s$  Solar absorption

$g_{tot}$  Total g-value

$R_s$  Solar reflectance

$F_c$  Shading factor

$F_c + g_{tot}$ : Value calculated with glass:  $0.72 / U_g = 1.6 \text{ W/m}^2 \text{ K}$ , DIN EN 13363-1


## Deep




01




02




03




05




06



07



08



10

Colours shown are not binding