Silent Gliss Fabrics&Components GmbH Rebgartenweg 5 79576 Weil am Rhein GERMANY

| Your message - reference | our reference | Gent |
|--------------------------|---------------|------------|
| ' <u>-</u> | PW/1120 | 2017-07-13 |

Certification report 17/1120

1. Description of the flooring:

| Product | Sunscreen made of on 3µm thick alu support and a 65%PVC/35%PES surface |
|-----------|--|
| Mass | 325 g/m² |
| Thickness | 0,45 mm |

2. Test results:

Classification according to EN 13501-1:2007+A1 (2009) based on:

| EN ISO 11925-2 (exposure=30s) | EN 13823 |
|-------------------------------|----------|

This report includes 2 pages and may only be reproduced in its entirety. The test results cover the received samples. Centexbel is not responsible for the representativeness of the samples.

Centexbel is a notified body N° 0493 for the European CPR (Construction Products Regulation) and for the European Directive related to Personal Protection Equipment.



| addressee | our reference | Gent | page |
|---------------------------------|---------------|------------|------|
| Silent Gliss Fabrics&Components | PW/1120 | 2017-07-10 | 2 |

3. Conclusion:

Referring to the means of control and the test results, the before mentioned product group can be classified as follows:

$$C - s2, d0$$

Mechanically fixed and free hanging over a 13 mm thick plasterboard (700 kg/m³ or more) and all substrates classified A1 and A2-s1,d0 which density is superior to 525 kg/m³

| Related commercial names to this product group | Aluscreen Futura |
|---|------------------|
| The obtained classification is based on the next test reports | CTB 17.01728.01 |
| Validity of the certificate | 18/06/2022 |

Petra Wittevrongel

Product Certifier